



Smart Visual Detection System



T +44 (0)1409 404050
E (general) info@seiche.com
E (commercial) enquiries@seiche.com
www.seiche.com



Technical Description

The SVDS camera system consists of: High Definition Video (HDV) and Long-Wave Infrared (LWIR) & thermal imaging camera pair, with on-board processing and storage. Each unit is housed robustly for maritime use. Various configuration options are available to ensure optimal visual coverage and ranges up to 360 degrees. If you have specific requirements, please contact enquiries@seiche.com.

General

- Modular customisable configurations
- Optional mounting systems
- Portable system deployed in hard case
- Fully marinised waterproof housing IP68 (pending certification)
- Hydrophobic glass
- Operating Temperature Range: -30°C to 70°C (pending certification)
- Shock: 1,500 g @ 0.4 msec (pending certification)
- Operating Voltage 19-30 VDC / supply voltage AC 110-240V
- Power consumption: Low power mode 20W Nominal 35W, Max Peak 135W
- On board GPU image processing 32GB on system storage
- On board Dual 4TB storage, main and encryption backup
- Networked removable storage up to 100TB
- Wi-Fi & satellite connectivity available on request
- GigE connectivity
- External triggers available 3.3V, 5V, 12V, serial optional protocol upon request
- Optional Workstations
- Built in 48 Channel GPS
- IMU orientation +/- 0.1°
- 360-visual scan with PTU

Software

- RTSP Video Streaming
- Automated File transfer for external network storage
- Fast logging
- Auto detection (customised training dependant)
- Pan and Tilt controls, including configuration, custom homing, and auto scan feature
- Mysticetus software compatibility (on request)

RGB Camera: Standard RGB camera (Optional upgrades):

- Sensor: 1/2.3 CMOS SONY IMX392
- Resolution: 2.4MP
- Array Size: 1920x1080
- Pixel Size: 3.45µm x 3.45µm
- Dynamic Range: 48dB
- Shutter Type: Global Shutter

Thermal camera:

- Thermal sensitivity: <40mK
- Pixel Pitch: 12 µm
- Full Frame Rate: 60 Hz
- Array size: 640 x 512
- f-number: 1.0
- Spectral Range: Long-wave Infrared; 7.5 µm – 13.5 µm
- Scene Dynamic Range: to 140 °C (high) to 500 °C (low)

Applications include:

- Consistent 24-hour marine mammal monitoring
- Utilizes advanced RGB and IR camera streams for effective hazard detection, small fishing boat identification, and vessel security, with user-friendly manual monitoring.
- First trained model for IR whale blow detection

Example of sperm whale fluke using Seiche's HD/IR camera

